

USB Hub KVM



Options

- DC power options : 12V / 24V / 48V / 125V


Benefits

- DB-15 KVM with 8 or 16 ports in 1U
- USB hub ports share peripheral devices among computers
- Local console & KVM ports support resolution up to 1920 x 1200
- Multi-platform for PC, server, Blade Server & SUN / MAC
- Port switching via OSD, front button & keyboard hotkeys
- Multi lingual OSD menu
- Hot pluggable, no software or drivers required




REACH

Basic Models - local console x 1




CV-801H




CV-1601H

KVM Port	
Port # :	8 or 16
Connector :	DB-15
Connectivity :	VGA + USB KB / MS 2-in-1 KVM cable (6 / 10 / 15 feet)
Resolution :	16:10 - max. 1920 x 1200 / 4:3 - max. 1600 x 1200
Local Console	
Graphic Connector :	1 x DB-15 VGA
Input device :	2 x USB type A for keyboard & mouse
USB hub 2.0 :	2 x USB type A for sharing peripheral devices among multiple computers
Resolution :	16:10 - max. 1920 x 1200 / 4:3 - max. 1600 x 1200

IP Models - local console + IP console



IP-802H




IP-1602H


IP Console	
Connector :	RJ45
User management :	1 x active user, 15-user login
Network protocol :	DHCP / BOOTP / DNS
Security :	SSL v3, RSA, AES, HTTP / HTTPS, CSR
Browser :	Internet Explorer
Resolution :	4:3 - max. 1600 x 1200

** IP console upgrade option for resolution support 1920 x 1080

Remote Models - local console + remote console



CV-802H



CV-1602H


Remote Console	
Connector :	RJ45
Connection :	via Cat5 / Cat6 cable to receiver box
Receiver box I/O :	VGA + 2 x USB type A for keyboard & mouse
Resolution :	16:9 - (1920 x 1080) Max. 50 meters 16:10 - (1920 x 1200) Max. 50 meters 16:10 - (1440 x 900) Max. 100 meters 4:3 - (1600 x 1200) Max. 100 meters 4:3 - (1280 x 1024) Max. 150 meters




Receiver box

USB hub connection


- USB Hub 2.0 :
2 x USB type A share peripheral devices among multiple computers




Local console & KVM port connection



IP console connection



Remote console connection



Management

Port switching	OSD, front button & keyboard hotkeys
----------------	--------------------------------------

Compatibility

Hardware	HP / IBM / Dell PC, Server and Blade Server SUN / Mac
OS support	Windows / Linux / Unix / Mac OS

Environment

Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Power

Input	Auto-sensing 100 to 240VAC, 50 / 60Hz
Consumption	Max. 18W

Compliance

Safety	FCC & CE certified
Environment	RoHS3 & REACH compliant

Physical

Product (W x D x H)	443 x 171 x 44 mm 17.4 x 6.7 x 1.73 inch
Packing (W x D x H)	500 x 400 x 90 mm 19.7 x 15.7 x 3.5 inch
Weight	Net 3 kg / 6.5 lb Gross 5 kg / 11 lb
Chassis color	Dark
Chassis materials	Steel