



# FRM220-10/100iS-2

Dual Channels 10/100Base-TX to 100Base-FX  
In-Band Managed Converter

The FRM220-10/100iS-2 is a dual (2 in 1) 10/100Base Ethernet to 100Base-FX fiber slide-in card converter based on the popular FRM220-10/100i. With advanced features like bandwidth control, this media converter is targeted for customer premises equipment in metro LAN, campus, enterprise and FTTx applications. By offering in-band management, this converter can be completely controlled and monitored from a centrally located managed rack controlling all converter settings including band-width control, duplex, and speed configuration. By offering two completely isolated converters on one card, this card can effectively double the conversion capacity of a rack.

## Features


- Dual independent converters 10/100Base-TX to 100Base-FX
- Auto-Negotiation or forced mode
- Auto MDI/MDIX
- Forward 2046 bytes (max.) packets in switch mode
- Supports IEEE 802.1Q Tag VLAN pass thru
- Supports Q in Q double tagged frame transparent
- Forward 9K jumbo packets in converter mode
- Supports local / remote In-band management (Monitor and Configure) by the SNMP manager (NMC)
- Bandwidth control (Nx32Kbps or Nx512Kbps) & flow control (Pause)
- Supports remote CPE power fail detect (dying gasp)
- Supports Far End Fault Indication (FEFI) and Link Fault Pass-Through (LFPT)
- Supports Loop Back Test and RMON counter
- D/D function for supported SFP fiber transceiver
- Auto Laser Shutdown (ALS) and Fiber Hardware Reset (FHR)
- Online local / remote f/w upgrade

## Specifications

<b>Optical Interface</b>	Connector	SFP LC x 2
	Data rate	125 Mbps
	Duplex mode	Full duplex
	Fiber	MM 50/125μm, 62.5/125μm. SM 9/125μm
	Distance	MM 2km, SM 15/30/50/80/120km, WDM 20/40/60/80km
<b>Electrical Interface</b>	Wavelength	MM 1310nm, SM 1310,1550nm WDM 1310Tx/1550Rx (type A) 1550Tx/1310Rx (type B)
	Connector	RJ-45 x 2
	Data rate	10Mbps, 100Mbps
<b>Electrical Interface</b>	Duplex mode	Half / Full duplex
	Cable	10Base-T Cat.3, 4, 5, UTP
		100Base-TX Cat.5, 5e or higher

<b>Standards</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, TS-1000
<b>Indications</b>	LED (Power, FEF, FX-Link, TX-SPD, TX-Duplex, TX-Link)
<b>Power Input</b>	12VDC
<b>Power Consumption</b>	< 4W
<b>Dimensions</b>	155 x 88 x 23mm (D x W x H)
<b>Weight</b>	130g
<b>Temperature</b>	0 ~ 50°C (Operating), -10 ~ 70°C (Storage)
<b>Humidity</b>	10 ~ 90% non-condensing
<b>Certification</b>	CE, FCC, RoHS compliant
<b>MTBF</b>	65,000 hrs

## Application



## Ordering Information

Model Name	Description
FRM220-10/100iS-2	Dual converter 10/100Base-TX to 100Base-FX SFP converter card with In-band management, (optional SFP)

**Note:** The Card is suitable for use in CH01 standalone chassis.